



# Standard Hollow Tine - .750MT x 5.500L x .520OD R523472



## Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

## Replaces

John Deere	TCU17450
R&R Products	R100-3634, RMT2965, RTCU17450
Toro	100-3634

## Specifications

Manufacturer	R&R Products
A - Tine Type	Standard Hollow
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	5.500 in (140mm)
D - Tine Tip Outside (Hole) Dia.	.520 in (13.2mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.049 in (1.2mm)
Savings	Volume Buy

## Fits Models

John Deere Aercore 1000  
John Deere Aercore 1500  
John Deere Aercore 2000  
John Deere Aercore 800  
Ryan GA30  
Toro ProCore 440

**Baber Turf Equipment Co.**

Unit 6 / 10 Firth Street Auckland, 2113  
09 294 6040

<https://baber.rrproducts.com/>



**Standard Hollow Tine - .750MT x 5.500L**  
**x .520OD**  
R523472



Toro ProCore 648  
Toro ProCore 660  
Toro ProCore 880  
Toro ProCore 648s