



# Alloy Machined Side-Eject Tine - .500MT x 4.000L x .370OD R523864



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.500 in (12.7mm)
C - Tine Length	4 in (102mm)
D - Tine Tip Outside (Hole) Dia.	.370 in (9.4mm)
E - Tine Tip Inside (Core) Dia.	.250 in (6.4mm)
F - Tine Wall Thickness	.065 in (1.7mm)

## Fits Models

Jacobsen Aero King 30  
Jacobsen GA-24  
Ryan GA30  
Ryan Greensaire II

**Baber Turf Equipment Co.**

Unit 6 / 10 Firth Street Auckland, 2113  
09 294 6040

<https://baber.rrproducts.com/>