

## Alloy Machined Side-Eject Tine - .472MT x 7.000L x .5400D



R9990032



### Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special highcarbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

#### Replaces

R&R Products

R999F007

#### **Specifications**

Manufacture	er	R&R Products
A - Tine Type	9	Alloy Machined Side-
		Eject
B - Tine Mou	Inting	.472 in (11.9mm)
Dia.		
C - Tine Leng	gth	7 in (178mm)
D - Tine Tip (	Outside	.540 in (13.7mm)
(Hole) Dia.		
E - Tine Tip I	nside	.400 in (10.2mm)
(Core) Dia.		
F - Tine Wall		.062 in (1.6mm)
Thickness		
Savings		Volume Buy
Dia. C - Tine Leng D - Tine Tip ( (Hole) Dia. E - Tine Tip II (Core) Dia. F - Tine Wall Thickness	gth Outside	.472 in (11.9mm) 7 in (178mm) .540 in (13.7mm) .400 in (10.2mm) .062 in (1.6mm)

#### **Fits Models** Redexim Verti-Drain

# **Baber Turf Equipment Co.** Unit 6 / 10 Firth Street Auckland, 2113

09 294 6040 https://baber.rrproducts.com/