



# Fimco Standard Spot Sprayer - 25 gal

RFLG29P



## Details

Fimco 15 and 25 gallon sprayers with corrosion resistant polyethylene tank feature lower tank profile for improved stability. Full drain out capability with molded-in drain port, cap and tether. Large pick-up sump. 5" fill lid with tether. 15' handgun hose. 18" lever handgun with adjustable pattern tip. 12 volt demand diaphragm 2.1 GPM; 60 psi. High-Flo pump. Maximum horizontal throw 30'. Maximum vertical throw 15'. Made in USA.

- 25 gallon corrosion-resistant polyethylene tank
- 5" fill lid with tether
- Full, drain-out capability wi/ molded-in drain port, cap & tether
- 15' handgun hose
- 18" lever handgun with adjustable pattern tip
- Large pick-up sump
- 12V demand diaphragm 2.1 GMP High-Flo pump
- 60 psi
- Both gallon and liter fluid volume indicator
- Molded wand clips
- Max horizontal throw: 30 ft.
- Max vertical throw: 15 ft.
- 8 ft. lead wire with Quick Connect
- 1 year warranty

## Specifications

Manufacturer	Fimco
Capacity	25 gal
Flow Rate	2.1 gpm
Material	Corrosion-Resistant Polyethylene
Maximum Pressure	60 psi
Spray Vertical Height	15 ft

**Baber Turf Equipment Co.**

Unit 6 / 10 Firth Street Auckland, 2113  
09 294 6040

<https://baber.rrproducts.com/>