

Alloy Hollow Side-Eject Tine - .750MT x 5.750L x .4700D



R108-9163



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

Toro

108-9163

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow Side-Eject
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	5.75 in (146mm)
D - Tine Tip Outside	.470 in (11.9mm)
(Hole) Dia.	
E - Tine Tip Inside	.300 in (7.6mm)
(Core) Dia.	
F - Tine Wall	.058 in (1.5mm)
Thickness	
Savings	Volume Buy

Fits Models

Toro Fairway Aerator Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880

Baber Turf Equipment Co. Unit 6 / 10 Firth Street Auckland, 2113

09 294 6040 https://baber.rrproducts.com/





Toro ProCore 648s

Baber Turf Equipment Co. Unit 6 / 10 Firth Street Auckland, 2113

Unit 6 / 10 Firth Street Auckland, 2113 09 294 6040 https://baber.rrproducts.com/