

Alloy Hollow Side-Eject Tine - .750MT x 5.750L x .660OD



R108-9165



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

Toro 108-9165

Specifications

Manufacturer R&R Products

A - Tine Type Alloy Hollow Side-Eject

B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 5.75 in (146mm) D - Tine Tip Outside .660 in (16.8mm)

(Hole) Dia.

E - Tine Tip Inside .500 in (12.7mm)

(Core) Dia.

F - Tine Wall .058 in (1.5mm)

Thickness

Savings Volume Buy

Fits Models

Toro Fairway Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Baber Turf Equipment Co. Unit 6 / 10 Firth Street Auckland, 2113 09 294 6040

https://baber.rrproducts.com/



R108-9165

Alloy Hollow Side-Eject Tine - .750MT x 5.750L x .660OD



Toro ProCore 648s

Baber Turf Equipment Co.Unit 6 / 10 Firth Street Auckland, 2113
09 294 6040

https://baber.rrproducts.com/