



Alloy Machined Side-Eject Tine - .375MT x 4.000L x .350OD R100-3625



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

Toro 100-3625

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.375 in (9.5mm)
C - Tine Length	4 in (102mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.236 in (6mm)
F - Tine Wall Thickness	.062 in (1.6mm)
Savings	Volume Buy

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648

Baber Turf Equipment Co.

Unit 6 / 10 Firth Street Auckland, 2113
09 294 6040

<https://baber.rrproducts.com/>



Alloy Machined Side-Eject Tine - .375MT
x 4.000L x .350OD
R100-3625



Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s