



D55 1in Part Circle Rotor - Electric Vih

Acme

RGWD55E2570A



Details

A full 4-inch pop-up clears tall turfgrass for even coverage. Stainless-steel riser resists damage and vandalism. Special design eliminates blow-by and reduces pressure loss to improve system performance. Dual-direction flushing protects internals from debris and ensures positive pop-up/down. Radius can be adjusted up to 25 percent for best coverage. Quick lock design allows internals to be serviced from the rotor's top. Range: 53' - 74'.

- A full 4-inch pop-up clears tall turfgrass for even coverage.
- Rolled-over flange keeps turfgrass clear of riser and nozzle.
- Stainless-steel riser resists damage and vandalism.
- Tough, commercial-grade plastic case stands up to punishment.
- Special design eliminates blow-by and reduces pressure loss to improve system performance.
- Dual-direction flushing protects internals from debris and ensures positive pop-up/down.
- Uniform coverage with square or triangular spacing.
- Full-circle and adjustable patterns for maximum flexibility.
- Easy arc adjustment in the field without any tools.
- Nozzle kit offers fully interchangeable nozzles and is included with each rotor.
- Unique manual On/Off control for hydraulic rotors.
- Heavy-duty spring assures positive retraction.
- Radius can be adjusted up to 25 percent for best coverage.
- Compact cartridge design allows for quick and easy repair.
- Quick lock design allows internals to be

Baber Turf Equipment Co.

Unit 6 / 10 Firth Street Auckland, 2113

09 294 6040

<https://baber.rrproducts.com/>



D55 1in Part Circle Rotor - Electric Vih

Acme

RGWD55E2570A



serviced from the rotor's top.

Specifications

Manufacturer	Weathermatic
Body Height	8.25 in
Exposed Cap	6 in
Diameter	
Inlet Size	1 in
Maximum Pressure	100 psi
Minimum Pressure	40 psi
Pop-up Height	4 in
Spinkler Flow	11.0 - 31.3 gpm
Sprinkler Operating Range	50 - 70 psi
Thread Type	ACME

Baber Turf Equipment Co.

Unit 6 / 10 Firth Street Auckland, 2113
09 294 6040

<https://baber.rrproducts.com/>