

Alloy Machined Side-Eject Tine - .750MT x 4.750L x .350OD

R201522



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side
	Eject
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	4.75 in (121mm)
D - Tine Tip Outside	.350 in (8.9mm)
(Hole) Dia.	
E - Tine Tip Inside	.250 in (6.4mm)
(Core) Dia.	
F - Tine Wall	.049 in (1.2mm)
Thickness	

Volume Buy

Fits Models

Savings

John Deere Aercore 1000 John Deere Aercore 1500 John Deere Aercore 2000 John Deere Aercore 800 Toro Greens Aerator Toro ProCore 1298 Toro ProCore 440

Baber Turf Equipment Co. Unit 6 / 10 Firth Street Auckland, 2113 09 294 6040

https://baber.rrproducts.com/



R201522

Alloy Machined Side-Eject Tine - .750MT x 4.750L x .350OD



Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880 Toro ProCore 648s

Baber Turf Equipment Co.Unit 6 / 10 Firth Street Auckland, 2113
09 294 6040

https://baber.rrproducts.com/